

Product datasheet Characteristics

Moisture Proof Bulk Head Light



Part Number	Shape	Wattage	Body Color	Voltage	Luminous Flux	Beam Angle	CRI	CCT	Rated Life	Length	Width	Height
ZL-BHRO20D-WH	Round	20W	White	AC110V / 220V	1800LM	180°	80	6500K	25000Hrs	210	210	60
ZL-BHRO20W-WH	Round	20W	White	AC110V / 220V	1800LM	180°	80	3000K	25000Hrs	210	210	60
ZL-BHRO20D-BK	Round	20W	Black	AC110V / 220V	1800LM	180°	80	6500K	25000Hrs	210	210	60
ZL-BHRO20W-BK	Round	20W	Black	AC110V / 220V	1800LM	180°	80	3000K	25000Hrs	210	210	60
ZL-BHROG20D-WH	Round With Grill	20W	White	AC110V / 220V	1800LM	180°	80	6500K	25000Hrs	210	210	60
ZL-BHROG20W-WH	Round With Grill	20W	White	AC110V / 220V	1800LM	180°	80	3000K	25000Hrs	210	210	60
ZL-BHROG20D-BK	Round With Grill	20W	Black	AC110V / 220V	1800LM	180°	80	6500K	25000Hrs	210	210	60
ZL-BHROG20W-BK	Round With Grill	20W	Black	AC110V / 220V	1800LM	180°	80	3000K	25000Hrs	210	210	60
ZL-BHROV20D-WH	Oval	20W	White	AC110V / 220V	1800LM	180°	80	6500K	25000Hrs	225	100	60
ZL-BHROV20W-WH	Oval	20W	White	AC110V / 220V	1800LM	180°	80	3000K	25000Hrs	225	100	60
ZL-BHROV20D-BK	Oval	20W	Black	AC110V / 220V	1800LM	180°	80	6500K	25000Hrs	225	100	60
ZL-BHROV20W-BK	Oval	20W	Black	AC110V / 220V	1800LM	180°	80	3000K	25000Hrs	225	100	60

Product datasheet Characteristics

Weatherproof Led Batten Light

PRODUCT SPECIFICATIONS

- ___Low Poer Consumption , High Efficiency
- ___Long Life Time
- ___PC Cover , ABS Base

CHARACTERISTICS

- ___Fit for Indoor And Outdoor use
- ___Used in Garages, Were Houses, Car Parkings, etc.
- ___PF > 0.9



Part Number	Type	Mounting distance	Dimension(MM)	Clips
ZL-WP-136AP	1 x 4feet T8	860	1266x88x94mm	8
ZL-WP-236AP	2 x 4feet T8	860	1266x130x94mm	8
ZL-WP-118AP	1 x 2feet T8	860	658x88x94mm	4
ZL-WP-218AP	2 x 2feet T8	860	658x130x94mm	4

